Create!™ **ULTIMA®, ULTIMA Health Zone™, and OPTIMA®**

Square Lay-in, Tegular & Vector®

fine texture



Ultima Create! Vector with Prelude® 15/16" suspension system (Pg. 259)

KEY SELECTION ATTRIBUTES

- · Artistic designs have broad appeal and complement unique interior design
- Mix and match designs with standard Ultima, Ultima Health Zone, and Optima
- Excellent sound absorption NRC 0.70 - 0.90
- · All the high performance benefits of Ultima or Optima fine-textured ceilings:
 - Water-repellent (Ultima Health Zone)
- · Product is directional
- · Custom samples available
- · Can contribute to LEED® credits

TYPICAL APPLICATIONS

- Classrooms
- · Libraries/media centers
- · Lobbies/reception areas
- Retail
- · Restaurant



CREATE!™ MAKES IT EASY TO CREATE UNIQUE, CUSTOM CEILING DESIGNS USING COLOR AND ARTWORK.

Original Artwork Guidelines:

- · Artwork must be vector-based
- · Acceptable file types:
- Adobe® Illustrator® .ai
- Encapsulated PostScript .eps
- Scalable Vector Graphics .svg
- · Acceptable Color Mode: CMYK

Original Digital Image Requirements:

- · Image must be 150 dpi at full print size
- · Acceptable file types:
- Joint Photographic Experts Group .jpg
 Tagged Image File Format .tiff

Solid Color Requirements:


- Choose from 100 color options suggested on Armstrong Create! sample*
- · Choose to match one of the RAL classic colors available on suspension systems and perimeter trims
- · Custom colors are available

* The Ultima/Optima colors and the Health Zone colors appear slightly different due to scrim surface texture.

SEARCH: Create

Adobe® Illustrator® is a registered trademark of Adobe Systems Incorporated.





armstrong.com/commceilings



Create![™] ULTIMA Health Zone[™], and OPTIMA®

Square Lay-in, Tegular & Vector®

fine texture

THEMES - AVAILABLE ON ALL CREATE! PANELS

Blooms



Single Panel Design 021



4-Panel Design
Design 022 (Add
A, B, C, or D for
individual panel



Single Panel Design 051



4-Panel Design
Design 052 (Add
A, B, C, or D for
individual panel
order)

Stars



Single Panel Single
Design 041 Design



Single Panel Design 042



Single Panel Design 043



Single Panel Design 011

Bubbles



Single Panel Design 012



Single Panel Design 013

WOOD LOOKS - AVAILABLE ON ULTIMA HEALTH ZONE CREATE! SQUARE LAY-IN PANELS Due to printing limitations, shade may vary from actual product.











Bamboo (BA)

Barnwood (BW)


Light Cherry (LC)

0ak (0K)

Walnut (WN)

COLOR REFERENCE CHART

Choose from the standard colors shown on the front of Create! 6" x 6" submittal samples. Keep in mind, sheen varies slightly depending on base panel selection (Ultima, Ultima Health Zone, Optima). Custom colors available.





Ultima Health Zone Create! in Walnut with coordinating suspension system and trim

COORDINATING SUSPENSION SYSTEM AND TRIM COLORS Due to printing limitations, shade may vary from actual product.

Custom RAL Colors



RAL Colors

See page 54 for a sampling of RAL colors.

Wood Looks



Barnwood (BW)







Light Cherry (LC)

0ak (0K)

Walnut (WN)



Create! $^{\text{\tiny TM}}$ – ULTIMA $^{\text{\tiny B}}$, ULTIMA Health Zone $^{\text{\tiny TM}}$, and OPTIMA $^{\text{\tiny B}}$

Square Lay-in, Tegular & Vector®

fine texture



Calculate LEED contribution at armstrong.com/greengenie

VISUAL SELECTION


PERFORMANCE Dots represent high level of performance.

Edge Profile	Item No.	Dimensions (Inches)	Acoustics		<u></u>	Anti-Mold & Mildew	Sag Resist	Cerified Low VOC Emissions	Durability		Recycled Content*	Recycle Program	Warranty⁺	
Suspension System			NRC	CAC	Fire Rating	②	*	Cerif VOC	~		<u>~</u>	Recy	4	Warı
ULTIMA or OPTIMA Create! Square Lay-in			(N) UL (Classified		BioBlock+	Humi- Guard+		Water Repel	Wash	Soil		Yes	No. of Years
for 15/16" Prelude XL	Z1910UC1	24 x 24 x 3/4"	0.70 ^{††}	35	Class A	•	•	•	-	•	•	High	•	30
	Z33520C1	24 x 24 x 3/4"	0.90††	26	Class A	•	•	_	_	•	•	High	•	30
ULTIMA Create! Tegular														
for 9/16" Silhouette XL ONLY; 1/4" or 1/8" Reveal	Z1912UC1	24 x 24 x 3/4"	0.70 ^{††}	35	Class A	•	•	•	-	•	•	High	•	30
ULTIMA or OPTIMA Create! Vector														
for 15/16" Prelude XL (White only)	Z1920UC1	24 x 24 x 3/4"	0.70 ^{††}	33	Class A	•	•	•	-	•	•	High	•	30
	Z39010C1	24 x 24 x 7/8" 🔲	0.80††	26	Class A	•	•	_	_	•	•	High	•	30
			•											
ULTIMA Health Zone Create! Square Lay-in														
for 15/16" Prelude XL	Z1935UC1**	24 x 24 x 3/4"	0.70 ^{††}	35	Class A	•	•	•	•	•	•	High	•	30
ULTIMA Health Zone Create! Tegular														
for 9/16" Silhouette XL ONLY; 1/4" or 1/8" Revea	Z1936UC1	24 x 24 x 3/4"	0.70 ^{††}	35	Class A	•	•	•	•	•	•	High	•	30
NOTE: Replacement panels may	vary slightly in color du	e to material variations ov	er time. Produc	t could hav	e slight color	r variation fro	m run to run;	adequate a	ttic stock sho	ould be order	red.			

Based on image/color coverage, NRC may vary slightly.

** Add 2-letter color suffix to item when specifying or ordering standard Wood Looks items. (e.g., Z1935UC1 L C)


SUSPENSION SYSTEMS AND EDGE DETAILS




Vector Panel and Prelude® XL® (White suspension required for Vector)



Tegular Panel and Silhouette® XL® 1/4" Reveal



Tegular Panel and Silhouette XL 1/8" Reveal



Lay-in Panel and Prelude® XL® or 360° Painted Grid

PHYSICAL DATA

Ultima/Ultima Health Zone: Wet-formed mineral fiber Optima: Fiberglass with DuraBrite® acoustically transparent membrane with CAC-backing

Surface Finish

Factory-applied latex paint with UV printing

Fire Performance ASTM E84 and CAN/ULC \$102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Ultima/Ultima Health Zone: Type III, Form 2, Pattern E

Optima: Type XII, Form 2, Pattern E Fire Class A

HumiGuard® Plus - superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Anti Mold/Mildew & Bacteria

AILL MOIO/MIIGEW & Bacteria
Ultima/Ultima Health Zone: BioBlock® Plus contains
an anti-microbial treatment and provides guaranteed
resistance against growth of mold/mildew and Grampositive and Gram-negative odor/stain-causing bacteria

for 30 years. Optima: Fiberglass substrate is inherently resistant to the growth of mold, mildew, and bacteria.

VOC Emissions

VOC Emissions
Ultima/Ultima Health Zone: Third party certified
compliant with California Department of Public Health
CDPH/EHLB/Standard Method Version 1.1, 2010. This
standard is the guideline for low emissions in LEED,
CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content*
Contains greater than 50% total recycled content.
Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

Ultima/Ultima Health Zone: R Factor – 1.6 (BTU units) R Factor – 0.28 (Watts units) Optima:

R Factor – 4.0 (BTU units) R Factor – 0.70 (Watts units)

30-Year Performance Guarantee & Warranty[†]

When installed with Armstrong Suspension System. 1-year limited warranty on color. Details at armstrong.com/warranty

Weight; Square Feet/Carton Ultima/Ultima Health Zone: 1.05 lbs/SF; 16 SF/ctn Optima: 0.55 lbs/SF; 16 SF/ctn

Minimum Order Quantity:

