

# KITCHEN ZONE™

Square Lay-in  
smooth texture



Kitchen Zone 24" x 24" panels

## KEY SELECTION ATTRIBUTES

- A better option to vinyl-covered gypsum:
  - Lower installed cost
  - Lightweight panels with 50% more pieces per carton
  - Easier to cut with less dust
  - Recyclable through Armstrong Recycling Program
- Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth (item 673)

## TYPICAL APPLICATIONS

- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

## DETAIL



1. Kitchen Zone Lay-in
2. Kitchen Zone Lay-in with Prelude 15/16" suspension system

## COLOR



White

# KITCHEN ZONE™

Square Lay-in  
smooth texture

UP TO **36%** RECYCLED CONTENT

LEED®

- acoustics
- energy
- daylight & views
- indoor air quality
- renewable materials
- recycled content
- waste mgmt
- local\* materials




Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie)

\*LOCATION DEPENDENT

## VISUAL SELECTION


## PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability				Recycled Content	Recycle Program	Warranty*	
				NRC	CAC						Water Repel	Wash	Scratch	Soil				
<b>KITCHEN ZONE</b>																		
15/16" Square Lay-in	1	<b>673</b>	24 x 24 x 5/8"	□	-	33	Class A	0.89	•	•	•	•	•	•	•	Std	•	30
	1	<b>672</b>	24 x 48 x 5/8"	□	-	33	Class A	0.89	•	-	•	•	•	•	•	Std	•	1

## SUSPENSION SYSTEMS

15/16"



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied vinyl latex paint

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

### ASTM E1264 Classification

Type IX, Form 2, Pattern G  
Fire Class A

### Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications (item 673)

### Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

### VOC Emissions

Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

### Application Consideration

Not designed for use in close proximity to commercial grease ducts.

### Insulation Value

R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

### 30-Year Performance Guarantee & Warranty<sup>1</sup>

When installed with Armstrong Suspension System (item 673). Details at [armstrong.com/warranty](http://armstrong.com/warranty)

### Cleaning Recommendations

To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth. Acceptable colorless disinfectants include:

- Sodium hypochlorite
- Hydrogen peroxide
- Quaternary ammonium

### Weight; Square Feet/Carton

672 – 0.82 lbs/SF; 96 SF/ctn  
673 – 0.82 lbs/SF; 64 SF/ctn

### Minimum Order Quantity

1 carton

