

# METALWORKS™

# Vector® & Vector Exterior

## smooth texture



MetalWorks Vector Exterior in Silver Grey with Prelude® XL® suspension system for Exterior Applications; RTC Bonneville Transit Center, Las Vegas, NV

# $\textbf{Color Selection} \quad \text{Due to printing limitations, shade may vary from actual product.}$



Panels are also available in Custom RAL colors upon request. NOTE: Effects colors are only available for items 6466M1 and 6466M3.

### Detail



MetalWorks Vector Microperforated



MetalWorks Vector Extra Microperforated



MetalWorks Vector Unperforated with Prelude 15/16" Exposed Tee suspension system

On the cover: MetalWorks Vector Microperforated in White with Prelude grid in White Financial institution, Boston, MA

# Key Selection Attributes

- Exclusive Vector-edge profile ceiling installs on new or existing 15/16" exposed tee suspension system resulting in a thin 1/4" reveal
- Outstanding NRC with acoustical fleece or infill panel (0.65 0.90)
- Durable Washable, Scrubbable, Impact-resistant, Soil-resistant
- Exterior system available, tested to meet wind uplift Classes 30, 60, and 90; less expensive than stucco for exteriors
- BioAcoustic™ infill panels can enhance acoustics and contribute to LEED® Credits
- Installs with minimal plenum clearance
- Standard edge caps for cut panels available in White, Silver Grey, Gun Metal Grey, and Black (for use with Effects™ colors)
- 100% downward accessible, without tools, plenum access per panel without the need of special tools
- For additional sizes, colors, and perforations, contact the Architectural Specialties project management team at 1 877 ARMSTRONG and select options 1-1-4



MetalWorks Vector Faceted Extra Microperforated in Effects Wood Looks Dark Cherry; Mount Saint Mary College, Newburgh, NY

# Perforation Options (Actual 1:2 scale shown)







(M3)

d Extra Microperforated

Additional sizes, colors, and perforations available as custom options. For more information, visit our web site at armstrong.com/metalworks or call 1 877 ARMSTRONG and select options 1-1-4 to work with the Architectural Specialties project management team.

Recycled Content: 25%armstrong.com/greengenie **LEED®** Credits **LEED** for Schools Energy Waste Recycled Acoustics Low Emitting Renewable Daylight Local Mgmt Content Materials Materials or CHPS 1

Location Dependen

## Colors and Perforations

White (WH) Silver Grey (SG) Gun Metal Grey (MY) Effects™ Maple (FXMP)

Effects Cherry (FXCH) Effects Dark Cherry (FXDC) Effects Walnut (FXWN) White Exterior (WH2)

Silver Grey Exterior (SG2) Gun Metal Grey Exterior (MY2) Effects Maple Exterior (FXMP2) Effects Cherry Exterior (FXCH2)

Effects Dark Cherry Exterior (FXDC2) Effects Walnut Exterior (FXWN2)

Unperforated (M1) Microperforated (M2) Extra Microperforated (M3)

# Visual Selection

# Performance Selection Dots represent highest level of performance.

	ltem Number*	Dimensions	% Open Area	Acoustics		12-14	Durable			
Edge Profile				NRC	CAC	Light Reflect (White only)			<b>9</b> ^^.	
METALWORKS™ Vector® (with acou	istical fleece)						Wash	Scrub	Impact	Soil
1/4" Reveal with 15/16" Vector	6466M1	2' x 2' 🔲	0%	0.10	36	0.77	•	•	•	•
	6466M2	2' x 2'	18.4%	0.70 0.90**	31*	0.61	•	•	•	•
	6466M3 <b>*</b>	2' x 2' 🔲	1.5%	0.65 0.70**	33*	0.77	•	•	•	•

- When specifying or ordering, include the appropriate letter color suffix with the item number (e.g., 6466 M 1 WH, 6466 M 3 E X CH, or 6466 M 1 E X M P 2). Light reflectance is for White only. Available in Effects Wood Looks finishes. NOTE: Perforation M2 is not available in Effects finishes as a standard option and has a 1,000 SF minimum order quantity.

- With optional field-cut #770 mineral fiber backing (cannot be used with fiberglass infill #8200100).

  NRC 0.90 (microperforated); NRC 0.70 (extra microperforated) with optional fiberglass infill #8200100 (cannot be used with #770 mineral fiber backing) NRC 0.85 (microperforated); or NRC 0.70 (extra microperforated) with optional BioAcoustic™ infill #5479 or 5823.


NOTE: Acoustical fleece on interior perforated panels only.

# Suspension Systems

	,
15/16"	Prelude® XL®
15/16"	Prelude XL for Exterior Applications† 12' Main Beam: 7301G90 2' Cross Tee: XL7321G90 10' Wall Molding: HD7801G90

<sup>†</sup> Available in Silver Grey (SG) and Gun Metal Grey (MY) colors as special order.

# Installation Details



Vector® & Vector Exterior

## smooth texture

Colors White (WH)

Black (BL)


Effects™ Maple (FXMP) Silver Grey (SG) Effects Cherry (FXCH) Effects Dark Cherry (FXDC) Effects Walnut (FXWN) Gun Metal Grey (MY)

### Accessories


Item Number	Description	Dimensions	Pieces/Carton
AX2STR	Axiom® Classic Trim - 2" Straight	120" x 3/4" x 2"	_
AX4STR	Axiom Classic Trim - 4" Straight	120" x 3/4" x 4"	_
AX6STR	Axiom Classic Trim - 6" Straight	120" x 3/4" x 6"	_
5342+†	2" Effects Wood Looks Trim	Nominal 10' length	6
5344 <b>+</b> †	4" Effects Wood Looks Trim	Nominal 10' length	6
5346 <b>+</b> †	6" Effects Wood Looks Trim	Nominal 10' length	6
FXVTBC	Vector T-Bar Connector Clip	N/A	10
FXSPTHDC	Effects Hold Down Clip for Cut Panel Installations	N/A	10
84008+	Vector Single-Slot Air Diffuser	2' x 2' (not available in Effects colors)	1
6098+	Edge Cap for Cut Panels	Nominal 2' length panels – use Black (BL) for Effects colors	50
5479	BioAcoustic™ Infill Panel (Beige Matte)	2' x 2' x 5/8"	12
5823	BioAcoustic Infill Panel (Black Matte)	2' x 2' x 5/8"	12
770**	Cortega® Square Lay-in Panel (White or Black Matte)	2' x 2' x 5/8"	8
8200100	1" Fiberglass Infill Bag (Black Gloss)	2' x 2' x 1"	12

- When specifying or ordering, include the appropriate two- or four-letter color suffix with the item number (e.g.,  $6098 \ \underline{W} \ \underline{H}$  or  $5342 \ \underline{F} \ \underline{X} \ \underline{C} \ \underline{H}$ ).
- Recommended for high CAC acoustical performance with MetalWorks Extra Microperforated panels.
- NOTE: Effects Wood Looks Trim cartons include FXSPLICE plates and FXTBC clips. For more information about Effects or Axiom trim options, visit armstrong.com/trim


# Accessory Details



**Axiom Classic Trim Application** 



**Effects Trim Application** 



Cutting MetalWorks Panel for Edge Cap

### Physical Data

# Material

Electrogalvanized Steel – 0.021" thickness

Surface Finish
Factory-applied powder-coated finish (post-coated).
Exterior: Factory-applied powder-coated finish
(post-coated on both sides). Effects finish on face only.
Premium and Custom RAL colors also available. Refer to
CS-3957 for a sampling of Custom RAL colors. Contact
Armstrong Architectural Specialties for custom color matching
requests at 1 877 ARMSTRONG, select options 1-1-4.

Fire Performance
Factory Mutual Approvals Specification tested per
ASTM E84 and CAN/ULC S102. Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

### **ASTM E1264 Classification**

Fire Class – Class A Unperforated – Type XX, Pattern G Perforated – Type XX, Pattern C

## **Installation Consideration**

For information about accessible faceted applications, refer to installation instructions on our web site at armstrong.com/installation.

#### Seismic Installations

MetalWorks Vector has been engineered, tested, and approved for application in all seismic areas.

# Wind Uplift Performance

MetalWorks Vector for exterior applications has been tested to meet wind uplift Classes 30, 60, and 90. Visit armstrong.com/metalworks or contact TechLine at 1.877 ARMSTRONG for installation instructions and test documentation.

One (1) year limited warranty. Details: armstrong.com/warranty

**Weight; Square Feet/Carton** 6466M1, 6466M3 – 1.15 lbs/SF; 40 SF/ctn 6466M2 – 1.10 lbs/SF; 40 SF/ctn

