


# CIRRUS® Second Look®

Scored Tegular  
medium texture



Cirrus Second Look III with Suprafine® 9/16" suspension system (Pg. 266)

## KEY SELECTION ATTRIBUTES

- Refined Cirrus texture
- Excellent score line painting for a clean visual
- Excellent sound absorption
- 94% Biobased content (see page 331)

## TYPICAL APPLICATIONS

- Offices
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Conference rooms
- Lobbies/reception areas
- Department stores/retail

## FACE VIEW



1. Cirrus Second Look I – Scoring creates nominal 12" x 12" squares
2. Cirrus Second Look II – Scoring creates nominal 24" x 24" squares
3. Cirrus Second Look III – Scoring creates nominal 6" x 48" linear planks

## DETAIL (Other Suspension Systems compatible. Refer to listing on page 158.)



1. Cirrus Second Look III
2. Cirrus Second Look III with Suprafine 9/16" suspension system

## COLOR



# CIRRUS® Second Look®

Scored Tegular  
medium texture

UP TO **63%** RECYCLED CONTENT

**LEED®**

acoustics energy daylight & views indoor air quality renewable materials recycled content waste mgmt local\* materials

**EPD** AVAILABLE For selected items only











Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie) \*LOCATION DEPENDENT




## VISUAL SELECTION

## PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Primary (Embodied) Energy	Recycled Content*	Recycle Program	Warranty
				NRC	CAC										
<b>CIRRUS Second Look I</b>															
15/16" Beveled Tegular 	14	<b>512</b>	24 x 48 x 3/4" 	0.65	35	Class A	0.85	BioBlock+	Std	•	Std	•	High	•	10
<b>CIRRUS Second Look II</b>															
9/16" Beveled Tegular 	28	<b>510</b>	24 x 48 x 3/4" 	0.65	35	Class A	0.85	•	Std	•	Std	•	High	•	10
15/16" Beveled Tegular 	14	<b>513</b>	24 x 48 x 3/4" 	0.65	35	Class A	0.85	•	Std	•	Std	•	High	•	10
<b>CIRRUS Second Look III</b>															
9/16" Beveled Tegular 	28	<b>511</b>	24 x 48 x 3/4" 	0.65	35	Class A	0.85	•	Std	•	Std	•	High	•	10
15/16" Beveled Tegular 	14	<b>514</b>	24 x 48 x 3/4" 	0.65	35	Class A	0.85	•	Std	•	Std	•	High	•	10

## SUSPENSION SYSTEMS



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

### ASTM E1264 Classification

Type III, Form 1, Pattern E I K  
Fire Class A

### Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

### VOC Emissions

Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

### Primary (Embodied) Energy

See all LCA information on our EPD's.

### High Recycled Content\*

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

### Insulation Value

R Factor – 1.9 (BTU units)  
R Factor – 0.33 (Watts units)

### Design Considerations

Do not mix Cirrus Second Look with standard Cirrus items in the same room.

### Warranty

Warranty details at [armstrong.com/warranty](http://armstrong.com/warranty)

### Weight; Square Feet/Carton

1.09 lbs/SF; 48 SF/ctn

### Minimum Order Quantity

1 carton

### Metric Items Available

512M, 510M, 513M, 511M, 514M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

