

# TRIMLOK®

## Screw Slotted Tee System

UP TO **50%** RECYCLED CONTENT  
armstrong.com/greengenie

**LEED®**

waste mgmt  
recycled content  
local\* materials

\*LOCATION DEPENDENT

### KEY SELECTION ATTRIBUTES

- Painted extruded aluminum construction for excellent corrosion resistance
- Threaded screw-slot reveal for easy partition attachment using a 5/16" – 18 N.C. thread screw
- Integral hook-type end detail for secure locked connection and easy removability
- 10-year limited warranty; 30-year limited warranty with **HumiGuard® Plus** products

### TYPICAL APPLICATIONS

- Offices
- Lobbies
- Corridors
- Conference rooms
- Non-magnetic areas/MRI suites

### VISUAL SELECTION

### PERFORMANCE

### PACKAGING

Face Profile	Item No.	Description	Dimensions (Inches)	Hanger Spacing*		Fire Guard™	Seismic Category	Pcs./ Ctn.	Lin. Ft./ Ctn.
				4 Ft.	5 Ft.				
<b>Trimlok Main Beams</b>									
9/16"	<b>2155</b>	12' ID Main Beam – Notched 24" O.C.	144 x 9/16 x 1-7/8"	12.84	–	–	–	24	288
9/16"	<b>2198</b>	10' ID Main Beam – Notched 60" O.C.	120 x 9/16 x 1-7/8"	12.84	–	–	–	24	240
9/16"	<b>2197</b>	10' ID Main Beam – Notched 30" O.C.	120 x 9/16 x 1-7/8"	12.84	–	–	–	24	240
9/16"	<b>2161</b>	5' Cross Tee – Unnotched	60 x 9/16 x 1-7/8"	–	–	–	–	48	240
9/16"	<b>2186</b>	5' Cross Tee – Center Notched	60 x 9/16 x 1-7/8"	–	–	–	–	48	240
9/16"	<b>2156</b>	4' Cross Tee – Center Notched	48 x 9/16 x 1-7/8"	11.01	–	–	–	48	192
9/16"	<b>2157</b>	4' Cross Tee – Unnotched	48 x 9/16 x 1-7/8"	11.01	–	–	–	48	192
9/16"	<b>2188</b>	30" Cross Tee – Unnotched	30 x 9/16 x 1-7/8"	–	–	–	–	48	120
9/16"	<b>2158</b>	2' Cross Tee – Unnotched	24 x 9/16 x 1-7/8"	73.51	–	–	–	48	96
9/16"	<b>2162</b>	20" Bridging Tee – Unnotched	20 x 9/16 x 1-7/8"	–	–	–	–	48	80
9/16"	<b>2163</b>	1' Bridging Tee – Unnotched	12 x 9/16 x 1-7/8"	–	–	–	–	96	96
<b>Molding</b>									
3/4"	<b>2128</b>	12' Angle Molding	144 x 3/4 x 3/4"	–	–	–	–	40	480
1/2"	<b>2129</b>	12' Shadow Molding	144 x 1 x 1 x 1/2"	–	–	–	–	40	480

\* Simple Span

ASTM Class  
HD - Heavy-duty  
ID - Intermediate-duty  
LD - Light-duty

### COLOR SELECTION



### DETAILS



TRIMLOK Main Beam

